

## A-1270 optical module



### Overview

10-Gigabit WDM/Bidi Singlemode SFP+ module from manufacturer Conexpro with wavelength (Tx/Rx) 1270/1330nm, speed 10 Gbps, equipped with one LC connector with UPC grinding and is intended for connection at a distance of up to 20 km. HUAWEI Optical Module DSFPX-A-1270/1330-1Km for FTTH & IP Network Model 34062899 offers reliable performance with a 1-year warranty. Perfect for fiber optic equipment. comUse one of the options below to locate your desired product. Speed of Optical PortFS Product Customis a customized service provided by FS to meet customers' hardware and software development needs, including product compatibility and software feature development for PicOS®, AmpCon, and transceivers. Add to Cart Product Highlights Built-in Semtech Chip, Max. Power Consumption 1W. OSP-SM10S is a pair of fiber optic transceivers for 1270/1330nm single-mode signals. Certified Transceiver — Kramer certified, hot-pluggable. Supports the single-fiber bidirectional function. For example, SFP-10G-ER-SM1270-BIDI must be used with SFP-10G-ER-SM1330-BIDI. This module can only be used on a switch running V200R009C00 or a later version. Wether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology.

## Article Content

ATGBICS SFP-GE-LX-SM1270-BIDI-C network transceiver module Fiber optic ...

Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Huawei SFP-GE-LX

10G CWDM SFP+ 1270-1330nm 10km DOM Transceiver Datasheet | FS

Description FS'' CWDM-SFP10G-10SP is a very compact 10Gb/s optical transceiver module for serial optical communication applications at 10Gb/s. The CWDM-SFP10G-10SP converts a 10Gb/s serial

CWDM Multiplexer

FS passive CWDM mux demux (4-18 channels) greatly saves optical fiber resources for scalable OTN systems with full use of coarse wavelength division multiplexing

10gbase Bidi SFP+ 1270nm Dfb 1330nm Pin 10km Simplex LC SMF

10gbase Bidi SFP+ 1270nm Dfb 1330nm Pin 10km Simplex LC SMF Transceiver Module, #A0047, Find Details and Price about Transceiver SFP+ from 10gbase Bidi SFP+ 1270nm Dfb

Conexpro 10G SFP+ optical module, WDM/BiDi, SM,

10-Gigabit WDM/Bidi Singlemode SFP+ module from manufacturer Conexpro with wavelength (Tx/Rx) 1270/1330nm, speed 10 Gbps, equipped with one LC connector with UPC grinding and is intended

FS 10GBASE-BX SFP+ 1330nm-TX/1270nm-RX 40km Transceiver

This 10G BiDi SFP+ transceiver, featured with data transmission over a single strand of fibre, the one transceiver transmits a 1330-nm channel and receives a 1270-nm signal, whereas the other BiDi

HUAWEI DSFPX-A Optical Module 1270/1330nm for FTTH & IP

HUAWEI Optical Module DSFPX-A-1270/1330-1Km for FTTH & IP Network Model 34062899 offers reliable performance with a 1-year warranty. Perfect for fiber optic equipment. | Alibaba .

10G SFP+ BIDI-70KM (Tx1270/Rx1330)

The 10G SFP+ BIDI-70KM (Tx1270/Rx1330) - OptiLink is an advanced bi-directional optical transceiver designed for single-fiber transmission up to 70KM. Operating

DIGITUS by ASSMANN Shop | SFP+ 10 Gbps Bi-directional Module ...

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product

#### 4 Channels 1270-1330nm Dual Fiber CWDM Mux Demux

Overview The CWDM Mux Demux support ITU-T G.694.2 wavelengths from 1270nm to 1330nm in 20nm increments. It is a flexible plug-and-play network solution that allows network operators to cost

#### SFP-10G-ER-SM1270-BIDI

Supports the single-fiber bidirectional function. Single-fiber bidirectional (BIDI) optical modules must be used in pairs. For example, SFP-10G-ER-SM1270-BIDI must be used with SFP-10G-ER-SM1330

#### TSFP-1270T-20-SMF

TSFP-1270T-20-SMF 10 Gigabit Optical Module > Single mode single fiber > LC port > 1270 nm sending, and 1330 nm receiving > Transmission distance up to 20 km

#### HK-SFP+-10G-20-1270

Actual product appearance and specifications may vary. \*Product performance is based on testing in a controlled environment. Your results may vary due to several external and environmental factors.

#### HK-SFP+-10G-20-1270

Single Power Supply 3.3V Digital diagnostic monitor compatible with SFF-8472 Single Fiber Bi-Direction LC Connector Hot Pluggable Capability Compliant With ROHS Standard Cost effective SFP solution,

#### 10Gb/s SFP+ BIDI 1270/1330nm 10km Optical Transceiver Module

Advantage of SULITON 10Gb/s SFP+ BIDI 1270/1330nm 10km Transceiver Module  
The sfp modules 10g provides an excellent solution for high reliability, lower power consumption and excellent EMI

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.activa.net.pl>

Email: [sales@activa.net.pl](mailto:sales@activa.net.pl)

Phone: +48 662 748 193

Address: ul. Cybernetyki 7B, 02-677 Warsaw, Poland

This document is for informational purposes only. Specifications subject to change without notice.

