

Dual-channel redundant fiber optic bus NT interface



Overview

EKS DL-CANR/2x13-SM-ST-L is a Dual Channel Redundant Ring CANbus to fiber repeater which can connect CAN field bus networks (e. CAN, CANopen, DeviceNet) via Single-mode fiber-optic cable in a Redundant -Ring topology to give network resilience and extend network distances . The special multifunctional fiber optic system DL CAN-R also allows the construction of optical ring structures. CAN, CANopen, DeviceNet) via multimode fiber optics. Optical Communication Modules are available for GE FANUC Series 90-70 Chassis Installation, or in modular Standalone. MIL-STD-1553 is a dual redundant bus, meaning that each channel has a BUS A and a BUS B. These buses cannot be treated as separate channels, but if a message is transmitted on Channel 0, BUS A and fails, the message can be re-transmitted on Channel 0, BUS B. Each channel will have a BUS A and a BUS. This series of products is a PROFIBUS DP protocol field bus fiber optic repeater, supporting PROFIBUS DP bus, independent dual bus electrical interface and two fiber interfaces, providing redundant dual bus structure and fiber redundant ring network function, for redundancy The dual-network system. Based on the original ideas of the CiA 307 document, a new standard has been developed, called dual-modular redundancy (DMR).

Article Content

Redundancy configuration using virtual Fibre Channel adapters

Similar to virtual Small Computer Serial Interface (SCSI) redundancy, virtual Fibre Channel redundancy can be achieved by using Multi-path I/O (MPIO) and mirroring at the client

GE Fanuc... Rev 6...PMD

OPTICAL COMMUNICATION For GE FANUC ETHERNET, GENIUS, MODBUS, and SNP Networks Phoenix Digital provides Redundant, Fault Tolerant, MULTIDROP Fiber Optic Communications for

GE Fanuc... Rev 6...PMD

Phoenix Digital provides Redundant, Fault Tolerant, MULTIDROP Fiber Optic Communications for GE Fanuc Ethernet, Genius™, Modbus, and Series 90™ Protocol (SNP) Communications.

modbus tools fiber products manual revision b.pmd

In non-redundant fiber optic networks configured for Auto-Recovery, such as open bus or single channel point-to-point network configurations, selection of a fiber optic Network Master module is optional,

MIL-STD-1553 Channel and Bus Function Specifications Explained

MIL-STD-1553 is a dual redundant bus, meaning that each channel has a BUS A and a BUS B. These buses cannot be treated as separate channels, but if a message is transmitted on

FO-1553-1 Teradyne (Single Channel, One Dual Redundant MIL

FO-1553-1 Single Channel, One Dual Redundant MIL-STD-1553 Fiber Optic Bus Extender from Teradyne | Buy Today from Artisan. 30-Day Return Guarantee. 1-Year Warranty.

Dual Redundancy Can-Bus Controller Design

II. DUAL REDUNDANCY CAN-BUS (DRC) NETWORK ARCHITECTURE The DRC Network architecture is shown in Fig.1. Compared with physical layer of a single-bus CAN network, physical

Industrial Rail 16 Channel DI/DO/AI/AO Optic Fiber Self

Industrial ring network optical transceiver provides up to 16 DI/DO/AI/AO channels for each node to be transmitted in optical fiber, and supports a variety of optical fiber

CAN Bus Redundant Ring Fiber Optic Converter Datasheet

The FO-FIB-100BT-R CAN bus to fiber optic converter provides an optical redundant ring network connection for CAN bus data interfaces on one or two, multi mode or single mode optical fibers.

Redundant Fiber Optic Networking Modules for PLC Networks

OCR This is not an IT switch. This is a networking module that control engineers can support, built for PLC networks, built for connecting Ethernet remote I/O, with fiber and redundancy by design.

Differences Between Industrial Ethernet Fiber Optic

As long as the fiber distances are under 2km in distances, this topology is superior in cost performance and reliability when compared to ring. This topology is shown

Fiber Optic Network Topologies for ITS and Other Systems

Networks can be configured in a number of topologies. These include a bus, with or without a backbone, a star network, a ring network, which can be redundant and/or self-healing, or some combination of

1:1 Redundant Multi-Channel Programmable 4GHz RF over Fiber

RFOptic's high reliability multi-channel programmable RFoF redundant system provides RF performance that is superior to the coaxial cable interface. The system is composed of 2 or 4 redundant auto

Redundant Bus Systems Using Dual-Mode Radio

Using the new dual-mode radio enables a redundant transmission line meeting all requirements with regard to real-time capability, robustness and transparency for the data bus. In addition, it provides a

MIL-STD-1553

NAI's MIL-STD-1553 communication smart function modules provide programmable 1, 2 or 4-channel and dual-redundant in transformer-coupled or direct-coupled interfaces and possess an improved

Spaceborne Fiber Optic Data Bus (SFODB)

TECHNOLOGY OVERVIEW SFODB is a revolutionary, high-speed spacecraft bus architecture based upon the commercial, Asynchronous Transfer Mode (ATM) telecommunications standard. The highly

Xie Ke launches Profibus redundant dual bus structure photoelectric ...

The unique dual-service and dual-fiber interface design of this device supports dual-network redundancy and fiber-optic ring networks, and supports point-to-point, star, chain bus, ring

DL-CANR/2x13-SM-ST-L

EKS DL-CANR/2x13-SM-ST-L is a Dual Channel Redundant Ring CANbus to fiber repeater which can connect CAN field bus networks (e.g. CAN, CANopen, DeviceNet) via Single-mode fiber-optic cable

Design of CAN Bus Dual Redundancy Scheme Based on FPGA

In view of the continuous expansion of the current CAN bus communication network, which brings a lot of problems such as paralysis of the communication network due to wiring failures, a dual

Dual-modular Redundancy for CAN networks

The CiA 307 document "Framework for maritime electronics" /1/ was the initial approach to use two CAN cables for mission-critical application in the year 2004. However, this standard was only applicable

Dual-modular Redundancy for CAN networks

Based on these requirements a CAN device supporting redundant communication shall have two CAN nodes (see figure 1). Each CAN node includes one DLL, one PCS and one PMA. Please note that

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.activa.net.pl>

Email: sales@activa.net.pl

Phone: +48 662 748 193

Address: ul. Cybernetyki 7B, 02-677 Warsaw, Poland

This document is for informational purposes only. Specifications subject to change without notice.

