

What is the OC48 optical module



Overview

The JDSU RoHS-compliant Small Form factor Pluggable (SFP) Optical Transceiver is a fully duplex serial electric, serial optical device with both transmit and receive functions contained in a single module that provides a high-speed serial link at signaling rates from 100 Mbps to 3.1 Gbps. The JDSU RoHS-compliant Small Form factor Pluggable (SFP) Optical Transceiver is a fully duplex serial electric, serial optical device with both transmit and receive functions contained in a single module that provides a high-speed serial link at signaling rates from 100 Mbps to 3.1 Gbps. Alcatel-Lucent 1665 DMX supports SR-1, LR-1, LR-2, CWDM, and DWDM OC-48 Pluggable Transmission Modules (PTMs). The following circuit packs support OC-48 PTMs. The following table lists the system specifications for OC-48 PTM interfaces. See Table 10-62, OC-48/STM-16 CWDM PTM wavelengths. The SFP-OC48-LR1-x-E10 SFP optical transceivers with digital diagnostics monitoring functionality provide a quick and reliable interface for OC-48/STM-16 single mode applications. The digital diagnostics functions are available via a 2-wire serial bus. In addition, they comply with the SFP Optical Transceiver—OC-48 for up to 80-km reach, OC-12 and Gigabit Ethernet for up to 120-km reach SFP Optical Transceiver—OC-48 for up to 80-km Reach, OC-12 and Gigabit Ethernet for up to 120-km Reach Key

Features • Supports line rate from 100 Mbps to 3.1 Gbps

- Compliant with SFP MSA INF-8074i Revision 1.0. The Cisco industry-standard Small Form-Factor Pluggable Interface Converter (SFP) for Packet-Over-SONET/SDH (POS), optical networking, and ATM applications (Figure 1) are hot-swappable optical interfaces that plug into a variety of ports on Cisco router interfaces. The FXC-SFPOC48-55-80 is an MSA-compliant transceiver, compatible with most switch and router. This Brocade® (Formerly) OC48-SFP-LR2 compatible SFP transceiver provides OC-48 (2488 mbps) transmission rates for up to 80 km over single-mode fiber (SMF) using a wavelength of 1550 nm via an LC connector.

Article Content

Delta Electronics Sonet OC-48/SDH Technical Specifications

View and Download Delta Electronics Sonet OC-48/SDH technical specifications online. RoHS Compliant Multi-Rate CWDM SFP Transceiver for SONET OC-48/SDH STM-16 with DDM Function.

Service Provider Cincinnati Bell Telephone Company LLC ...

2.2 OC-48/STM-16 Channels consist of Channel Terminations (CTs), interoffice Fixed and Per-mile mileage elements and optional features and functions which provide optical interconnection between

OC-48 PTM optical specifications

CWDM optical path penalty includes effects of dispersion, reflection, and jitter and a 0.3 dB penalty due to optical filters and cross-talk. The CWDM target distance is dispersion-limited at the 1611 nm

Cisco 7600 Series 1-Port OC-48c/STM-16 POS/SDH OSM

CISCO 7600 SERIES 1-PORT OC-48C/STM-16 POS ENHANCED OPTICAL SERVICES MODULE High-Density OC-48c/STM-16 Connectivity for Consolidated Service Provider POPs with Service

DATASHEET MODULETEK:SFP-OC48-SR-x-D10 OC-48SR/STMI

Overview 6 SFP optical transceivers are designed to comply with SONET/SDH standards at OC-48 SR/STM-16 (2.488Gb/s) data rate. The SFP-OC48-SR-x-D10 SFP optical transceivers with digital

Fiber Optic Transceiver SFP OC48, 80 km reach, 1550nm Specifications

Fiber Optic Transceiver SFP OC48, 80 km reach, 1550nm from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors,

Cisco SFP-OC48-SR Datasheet

Cisco SFP-OC48-SR The Cisco industry-standard Small Form-Factor Pluggable Interface Converter (SFP) for Packet-Over-SONET/SDH (POS), optical networking, and ATM applications (Figure 1) are

Fiber Optic Transceiver SFP OC48, 80 km reach, 1550nm Specifications

The L-com FXC-SFPOC48-55-80 is an SFP form-factor transceiver, supporting OC48 data rates. The L-com FXC-SFPOC48-55-80 features a 1550nm transmitter and supports 80 km links over single mode

DATASHEET MODULETEK:SFP-OC48-IR1-x-D10

Overview ModuleTek's SFP-OC48-IR1-x-D10 SFP optical transceivers are designed to comply with SONET/SONET and Gigabit Ethernet IEEE 802.3. The SFP-OC48-IR1-x-D10 SFP optical

Oc48-sfp-sr1-c Datasheet

It is guaranteed to be 100% compatible with the equivalent Brocade® (Formerly) transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and

Cisco 1-Port Channelized OC-48/STM-16 Shared Port Adapter

This data sheet contains the specifications for the Cisco 1-Port Channelized OC48/STM-16 SPA (refer to Figure 1). Figure 1. Cisco 1-Port Channelized OC48/STM-16 Shared Port Adapter

Oc48-sfp-lr2-c Datasheet

At the heart of our company is the ability to provide state-of-the-art optical transport and connectivity solutions that are compatible with more than 100 optical switching and transport platforms.

Cisco SFP-OC48-IR1 Duplex SFP 2.67Gbps 15 km SMF DDM 1310nm

The Cisco SFP-OC48-IR1 1000BASE-LX/LH Ethernet transceiver is a Duplex SFP transceiver for optical communications, rated for distances up to 15 km and a maximum bandwidth of 2.67Gbps.

ProductSpecification

Description cation applications. It features a Duplex LC optics interface and supports standard AC-coupled CML for high-speed signal transmission, along with LVTTTL control and monitor signals. This

SFP Optical Transceiver OC-48 for up to 80-km reach, OC-12 and

The JDSU RoHS-compliant Small Form factor Pluggable (SFP) Optical Transceiver is a fully duplex serial electric, serial optical device with both transmit and receive functions contained in a single

Designing with Agilent's SFF LC OC-48 Fiber Optic Transceiver

The fiber optic transceivers are meant for single mode operation at a center wavelength of 1310nm, with output power of -5dBm. The short reach module is fabricated with a Fabry Perot (FP) laser while the

Alcatel-Lucent Documentation Library

OC-48 PTM optical specifications Purpose Alcatel-Lucent 1665 DMXtend supports SR-1, LR-1, LR-2, CWDM, and DWDM OC-48 Pluggable Transmission Modules (PTMs). The following circuit packs

Part 1: OC-48, OC-192, and beyond

SONET (synchronous optical network) plays an important role in OC-48. New OC-48 and OC-192 designs tend to use it because it is the established protocol for traffic at this rate at the core.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.activa.net.pl>

Email: sales@activa.net.pl

Phone: +48 662 748 193

Address: ul. Cybernetyki 7B, 02-677 Warsaw, Poland

This document is for informational purposes only. Specifications subject to change without notice.

